

Undersea Power Technology

Kenneth E. Rogers
Space and Naval Warfare Systems Center, Code D714
San Diego, CA 92152-5001
Ph: (619) 553 1521, Fax: (619) 553 5229, email: kr Rogers@spawar.navy.mil
Award # N0001499WX30365

LONG TERM GOALS

The goal of this project is to develop renewable undersea power sources for floating, suspended, and bottomed surveillance and environmental sensors and communication devices.

OBJECTIVES


SSC-SD will provide engineering and test support to Ocean Power Technologies (OPT) in the development, testing, and evaluation of an energy harvesting electric EEL.

APPROACH

In collaboration with OPT and their academic partners, SSC-SD will (1) prepare appropriate test plans to determine EEL performance in various flow configurations; (2) operate a high-speed water tunnel in support of the defined tests; and (3) prepare data reports documenting the results.

WORK COMPLETED

Ken Rogers and Greg Anderson attended the project review held at OPT on 1 July 1999. Mr. Anderson made a presentation on the SSC-SD high speed water tunnel (figure 1) proposed for




1. Water Tunnel Test Section

advanced EEL testing. Subsequent discussions were conducted between OPT personnel and Mr. Dan Ladd of SSC-SD regarding planning for tests to be conducted in the water tunnel during the first half

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 1999		2. REPORT TYPE		3. DATES COVERED 00-00-1999 to 00-00-1999	
4. TITLE AND SUBTITLE Undersea Power Technology				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Space and Naval Warfare Systems Center, Code D714, San Diego, CA, 92152				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 3	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

of FY2000. An Argon-Ion laser is being re-gassed in preparation for use of the Laser Doppler Velocimeter (LDV) to measure flow velocity in any (laser) accessible point in the test section. Hardware has been designed and is being fabricated to mount the test EELs in the SSC-SD water tunnel. Figure 2 is a rendering of the adjustable mount fixtures inside an existing acrylic water tunnel liner. Provisions have been made for dye ejection ports, in the upstream bluff body. Hydrogen bubble wire visualization is also possible with minor modification.



2. *Rendering of SSC-SD test hardware, showing the EEL downstream from the bluff body. Flow is from left.*

RESULTS

No tests have been conducted to date.

IMPACT/APPLICATIONS

Although the amount of power available in a slow-moving stream is small, modern ultra-low-power electronic sensors and instrumentation packages may eventually be operable with only a few milliwatts of power. Such power could be provided by a renewable power source such as the EEL. The advantages of a renewable power source over a primary battery may include

- Higher total energy per device volume or mass
- Longer shelf life
- Greater safety in handling and storage
- Lower cost
- More efficient packaging

Larger versions of the EEL could conceivably be built to power more conventional instrumentation requiring higher power levels. They would compete directly with advanced low-water-speed turbines such as the Gorlov helical turbine.

TRANSITIONS

A successful demonstration of an electric EEL should lead to a transition to an appropriate technology development project in undersea instrumentation or sensing.

RELATED PROJECTS

Depending on the power achievable from an advanced EEL, several current projects may be beneficiaries of this technology. These include surveillance projects in the ONR Off-board and Deployable Systems Program (321SS), as well as those dedicated to the development of long-term environmental measurements.

REFERENCES

None

PUBLICATIONS

None

PATENTS

None